



Product Facts

\$ Save energy and cost: i.e. Over 80% reduction in energy consumption compared to standard halogen downlights.



Hassle free: Lasts for over 40,000 hours.



5 year warranty: Truly delivering your return on investment.



Approved: SAA/C-tick (RCM), RoHS, CE.



Healthy: No IR or UV Radiation.



45° beam angle: Ideal for showrooms and feature lighting.



Where: Commercial, Domestic, Retail, Healthcare and many more applications.



POWER-LITE™ P1

DL13WCOB-AG

Why POWER-LITE™ LED COB DOWNLIGHT

The POWERLITE™ LED COB Downlight not only provides a lifelong lighting solution, saving in energy and maintenance costs, but produces only a minimal amount of heat compared with standard halogen downlights. The LED COB technology delivers a smart look in areas such as showrooms, waiting rooms etc, where first impressions matter.



CLICK HERE TO:

ORDER

REQUEST FURTHER INFO

DOWNLOAD PHOTOMETRIC DATA



Key Benefits

- The POWER-LITE™ LED range has been developed over the past 6 years, working closely with the production team to bring an energy saving lighting solution within your reach.
- Slimline, compact design makes the installation easy and improves the aesthetics of the project.
- With our global certification process, this product carries CE, RoHS, SAA/C-tick (RCM) certification, ensuring compliance.
- The POWER-LITE™ 5 year Downlight warranty is provided to ensure peace of mind and truly delivers your return on investment, whether utilising these units in new installations or retrofit projects.

Specifications & Dimensions

	DL13WCOB-AG-CW	DL13WCOB-AG-NW
Power:	13W	13W
Approvals:	SAA/C-tick (RCM), RoHS, CE	SAA/C-tick (RCM), RoHS, CE
LED Chip:	Citizen COB	Citizen COB
Lumens:	850 LM	835 LM
Beam Angle:	45°	45°
Cut out:	95-100mm	95-100mm
LED Color Temperature:	5000K	4000K
Warranty:	5 Years	5 Years
Driver:	Dimmable	Dimmable
Life Span:	40,000 hours	40,000 hours
Frame Colour:	White	White
Connection Included:	LED Driver, lead and plug	LED Driver, lead and plug
Dimensions:	Ø 110mm x 100mm	Ø 110mm x 100mm
IP Rating:	IP20	IP20
Operating Temperatures:	-20°C to 45°C	-20°C to 45°C
UGR:	<19	<19
CRI:	>80	>80
Voltage:	AC200-265V	AC200-265V
Carton Quantity:	24	24

Note: IC-F / IC-4 rated downlights, can be covered and abutted with building materials which can be safely exposed to temperatures of up to 90°C.

CLICK HERE TO:

ORDER

REQUEST FURTHER INFO

DOWNLOAD PHOTOMETRIC DATA