



## Product Facts



**Safe & User Friendly:** Overload protection, overcurrent protection and over temperature protection.



**Approved:** SAA, AS/NZS 3100, AS/NZS 3133, IEC 60669-2-1



**Where:** Used on all residential and commercial lighting installations.



**5 Year Warranty:** Truly delivering your return on investment.

## Specifications & Dimensions

### DS-R

Power:	10-350VA
Voltage:	AC 220-240V~ 50Hz
Min/Max Load:	LED 10VA-150VA , Halogen/Incandescent 10VA-350VA
Dimming Operation:	Trailing Edge
Operating Temperature:	-20°C to 80°C
Humidity:	<75%
Over Temperature Protection:	Manual reset
Compatible Loads:	Power-Lite LED Luminaires*
Dimming Range:	3% to 100% (Load Dependent)
Product Approvals:	SAA
Warranty:	5 Year Warranty
Colour:	White
Carton Quantity:	200

\*\*Face plate and switch not included.



DS-R

\*Note: Due to the vast range of LED luminaires currently on the market, POWER-LITE is unable to take liability or responsibility for any incompatibility or warranty issues arising from the use of POWER-LITE dimmers with non-POWER-LITE products.

[CLICK HERE TO:](#)

[ORDER](#)

[REQUEST FURTHER INFO](#)