POWER-LITE™
LED FLOOD LIGHTS

LED-SFL

E2362

POWER-LITE™ 5 Year Warranty

Product Facts

Save energy and cost: i.e. 30W LED Driveless Flood Light replaces a 150W Halogen providing an 80% energy saving.

Call today: For a quote or a free energy assessment/payback plan: **1800 909 306** or email: **sales@nedlandsgroup.com.au**.

5 year warranty: Truly delivering your return on investment.

Approved: SAA/C-tick ROHS, CE.

Healthy: No IR or UV Radiation.

Flexible: IP65 Waterproof with glass lens provides multiple applications and longevity.

Where: Greenstar and NABERS environments, Warehouses, Fuel and Toll Stations, Retail, Recreation, Education, Commercial, Production, Advertisement and many more.

LED-SFL10W-W
(Also avaliable in black)

LED-SFL30W-B
(Also avaliable in white)

POWER-LITE™ P1

Why POWER-LITE™ LED

Utilising the POWER-LITE™ LED Flood Light provides many benefits in addition to the substantial costs savings achieved through our LED technology. Our LED Flood Lights tackle the usual challenges faced with providing a lighting solution, including the elimination of UV therefore insects will not be attracted to this light. There is no warm up process, the light is immediate and reaches full output upon the flick of a switch. The IP65 rating and high quality powder coating provides a durable and safe solution, protecting the product against rust and water penetration, meaning no maintenance is required.

CLICK HERE TO: ORDER | REQUEST FURTHER INFO | DOWNLOAD PHOTOMETRIC DATA

NEDLANDS GROUP

Free Call 1800 909 306
Fax +61 3 8669 4097
Website nedlandsgroup.com.au
Sales sales@nedlandsgroup.com.au
Service service@nedlandsgroup.com.au

POWER-LITE™
LED FLOOD LIGHTS

LED-SFL

E2362

POWER-LITE™ 5 Year Warranty

Key Benefits

- The POWER-LITE™ LED range has been developed over the past 5 years, working closely with the production team to bring an energy saving lighting solution within your reach.
- With our global certification process, this product carries CE, SAA/C-tick (RCM) certification ensuring compliance.
- The POWER-LITE™ 5 year Flood Light warranty is provided to ensure peace of mind and truly delivers your return on investment, whether utilising these units in new installations or retrofit projects.

Specifications & Dimensions

	LED-SFL10W-W	LED-SFL30W-W	LED-SFL10W-B	LED-SFL30W-B
Power:	10W	30W	10W	30W
IP Rating:	IP65	IP65	IP65	IP65
Approvals:	SAA/C-tick, RoHS, CE	SAA/C-tick, RoHS, CE	SAA/C-tick, RoHS, CE	SAA/C-tick, RoHS, CE
Voltage:	AC 85-265V	AC 85-265V	AC 85-265V	AC 85-265V
Power Factor:	> 0.90	> 0.90	> 0.90	> 0.90
Material:	Aluminium Die-Casting	Aluminium Die-Casting	Aluminium Die-Casting	Aluminium Die-Casting
Lumens*:	900 LM	2,800 LM	900 LM	2,800 LM
Replaces:	60W Halogen	150W Halogen	60W Halogen	150W Halogen
Beam Angle:	120°	120°	120°	120°
Size:	150 x 92.5 x 23mm	270 x 185 x 30mm	150 x 92.5 x 23mm	270 x 185 x 30mm
LED Color Temperature:	Cool White (6400K)	Cool White (6400K)	Cool White (6400K)	Cool White (6400K)
Light Source / LED Chip:	Epistar	Epistar	Epistar	Epistar
LED Driver:	Internal	Internal	Internal	Internal
Warranty:	5 Years	5 Years	5 Years	5 Years
Life Span:	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours
Nett Weight:	0.60kg	1.8kg	0.60kg	1.8kg
Connections:	50cm Power Cable	50cm Power Cable	50cm Power Cable	50cm Power Cable
Frame Colour:	White	White	Black	Black
Qty / Carton	20	10	20	10

* : The actual effects of the lumen output will depend on the application and environment, replacement wattage is approximate
Note: If this fitting is installed outdoors, please remove plug and hard wire into waterproof connection.

Notes and Next Action

CLICK HERE TO: ORDER | REQUEST FURTHER INFO | DOWNLOAD PHOTOMETRIC DATA

NEDLANDS GROUP

Free Call 1800 909 306
Fax +61 3 8669 4097
Website nedlandsgroup.com.au
Sales sales@nedlandsgroup.com.au
Service service@nedlandsgroup.com.au